



LED 3528 WATERPROOF FLEX TAPE

SPECIFICATIONS

Equivalent Source	Up to 150W incandescent Rope Light
L70 lumen depreciation up to	50,000 hours
Wattage	1.5W per foot/25W per roll
Chip	3528
Beam Spread	120°
Operating Temperature	-4°F to +104°F (-20°C to +40°C)
Number of LED's	60pcs
Voltage	12V or 24V
Frequency Range	50-60Hz
LED Source	SMD3528
Power Factor	>90%
Efficiency	80-100LM/W
IP	IP64 or IP67
Warranty	3 year limited
Length	16.4ft (5M)

Caution:

- *Turn power off before inspection, installation, or removal
- *Suitable for Wet Locations.
- *This device is not intended for use with emergency exit fixtures or emergency exit lights.

BENEFITS

- 1.5 watts per foot = 25 watts per roll
- Maintenance free operation lasts up to eight times longer than conventional lighting.
- Suitable for wet locations.
- Available from 2700-6000 CCT and RGB
- Low heat, low maintenance.
- Compatible with most magnetic and electronic transformers.

ACCESSORIES

- Extrusions
- Diffusers
- Power Supplies
- Connectors
- Dimmers
- Controllers

APPLICATIONS

- Cove Lighting
- Under Counter Lighting
- Inside Cabinet Lighting
- Accent Lighting
- Outdoor accent Lighting
- Applications are endless

EXAMPLE: ORDERING INFORMATION \ \ LLP SMD 3528 - 12V - 60PCS – WW - WP

Family	Product	Chip	Voltage	LED Per Meter	Color (CCT)		IP Rating	Environment
LLP	SMD	3528	12V	60 PCS	RGB	Multi-Color	WP - Waterproof	IP64
			24V	60PCS	WW	Warm White	HD – Heavy Duty	IP67
					NW	Neutral White		
					CW	Cool White		



Prepared By:

Product Code:

Project:

Date: