Prepared By:	Product Code:	
Project:		Date:





SPECIFICATIONS

SI ECII ICATIONS						
Equavalent Source	Up to 150W incandescent Rope Light L70 Lumen					
L70 lumen depreciation up to	50,000 hours					
Wattage	4.4W per foot/25W per roll					
Chip	5060					
Beam Spread	120°					
Operating	-4°F to +104°F (-20°C to					
Temperature	+40°C)					
Number of LED's	60pcs					
Voltage	12V or 24V					
Frequency Range	50-60Hz					
LED Source	SMD50690					
Power Factor	>90%					
Efficiency	80-100LM/W					
IP	IP20					
Warranty	3 year limited					
Length	16.4ft (5M)					

Caution:

- *Turn power off before inspection, installation, or removal
- *Not suitable for Wet Locations.
- *This device is not intended for use with emergency exit fixtures or emergency exit lights.

LED 5060 INDOOR FLEX TAPE

BENEFITS

- 4.4 watts per foot = 72 watts per
- Maintenance free operation lasts up to eight times longer than conventional lighting.
- Available from 2700-6000 CCT and RGB
- Low heat, low maintenance.
- Compatible with most magnetic and electronic transformers.

ACCESSORIES

- Extrusions
- Diffusers
- Power Supplies
- Connectors
- Dimmers
- Controllers

APPLICATIONS

- Cove Lighting
- Under Counter Lighting
- Inside Cabinet Lighting
- Accent Lighting
- Applications are endless

EXAMPLE: ORDERING INFORMATION \\ LLP SMD 5060 - 12V - 60PCS - WW

Family	Product	Chip	Voltage	LED Per Meter	Color (CCT)		Environment
LLP	SMD	5060	12V	60 PCS	RGB	Multi-Color	IP20
			24V	60PCS	WW	Warm White	
					NW	Neutral White	
					CW	Cool White	



