

Prepared By:	Product Code:
Project:	Date:



LED X STREET LIGHT SERIES 100W, 150W, 200W, 300W

PRODUCT DESCRIPTION

- *FCC, ETL listed
- * Power: 100W, 150W, 200W, 300W
- * Input Voltage: AC100-277V or AC200-480V
- * Lighting Angle: Type II, Type III, Type IV, Type V
- * Photocell, Shorting cap, Motion sensor, Surge protection available
- * Arm Mount, Slip Fitter, Slip Fitter Adapter and Trunnion available
- * Easy installation

APPLICATIONS

Streets, Parks, Parking Lots and etc.

SPECIFICATIONS

Power	100W	150W	200W	300W
Product Size	13"x12"x3.6"	18.2"x12"x3.6"	18.2"x12"x3.6"	22.9"x12"x3.6"
LED Chip	SMD3030	SMD3030	SMD3030	SMD3030
Input Voltage	AC100-277V/AC200-480V			
Frequency	50/60Hz	50/60Hz	50/60Hz	50/60Hz
PF	0.9	0.9	0.9	0.9
Efficiency	130lm/w	130lm/w	130lm/w	130lm/w
LED Luminous Flux	13000lm	19500lm	26000lm	39000lm
CCT	4000K /5000K /5700K			
CRI	Ra>80			
LED Node Temperature	<85°C			
Operation Temperature	-30~+45°C			
Storage Temperature	-40~+80°C			
IP Grade	IP65			
LED Lifespan	50,000Hours			
Driver	Built-in			
Lighting Angle	Type II, Type III, Type IV, Type V			
Multi-functions	Photocell, Shorting Cap, Motion Sensor, Surge Protection Available			
Installation Available	Arm Mount(For Square or Round Pole), Slip Fitter, Slip Fitter Adapter and Trunnion available			

