

| | |
|--------------|---------------|
| Prepared By: | Product Code: |
| Project: | Date: |



LED X STREET LIGHT SERIES 100W, 150W, 200W, 300W

PRODUCT DESCRIPTION

- *FCC, ETL listed
- * Power: 100W, 150W, 200W, 300W
- * Input Voltage: AC100-277V or AC200-480V
- * Lighting Angle: Type II, Type III, Type IV, Type V
- * Photocell, Shorting cap, Motion sensor, Surge protection available
- * Arm Mount, Slip Fitter, Slip Fitter Adapter and Trunnion available
- * Easy installation
- * 5 Year Warranty

APPLICATIONS

Streets, Parks, Parking Lots and etc.

SPECIFICATIONS

| Power | 100W | 150W | 200W | 300W |
|------------------------|--|----------------|----------------|----------------|
| Product Size | 13"x12"x3.6" | 18.2"x12"x3.6" | 18.2"x12"x3.6" | 22.9"x12"x3.6" |
| LED Chip | SMD3030 | SMD3030 | SMD3030 | SMD3030 |
| Input Voltage | AC100-277V/AC200-480V | | | |
| Frequency | 50/60Hz | 50/60Hz | 50/60Hz | 50/60Hz |
| PF | 0.9 | 0.9 | 0.9 | 0.9 |
| Efficiency | 130lm/w | 130lm/w | 130lm/w | 130lm/w |
| LED Luminous Flux | 13000lm | 19500lm | 26000lm | 39000lm |
| CCT | 4000K /5000K /5700K | | | |
| CRI | Ra>80 | | | |
| LED Node Temperature | <85°C | | | |
| Operation Temperature | -30~+45°C | | | |
| Storage Temperature | -40~+80°C | | | |
| IP Grade | IP65 | | | |
| LED Lifespan | 50,000Hours | | | |
| Driver | Built-in | | | |
| Lighting Angle | Type II, Type III, Type IV, Type V | | | |
| Multi-functions | Photocell, Shorting Cap, Motion Sensor, Surge Protection Available | | | |
| Installation Available | Arm Mount(For Square or Round Pole), Slip Fitter, Slip Fitter Adapter and Trunnion available | | | |

